



**ROGUE
PUMP®**

MAX TRS-33S Specifications

Pump Specifications

Type
Impeller
Stage Number
Flow-rate @ 0' Head
Head Maximum
Suction Lift
Optimum Efficiency
Liquid Temperature
Liquid Viscosity
Liquid Specific Gravity
Solids Diameter
Shaft Seal Type
Fitting Dimensions
Inlet
Outlet
Weight
Pump & Motor

English/Metric

**Centrifugal Pump
Open
Single
47gpm / 178 lpm
45' / 13.72m
6' / 1.83m
34-14gpm @ 20'-36'
200°F /93°C maximum
100 SSU maximum
1.1 - 1.3
3/8" / 9.53mm
Mechanical Seal

1.5" / DN 40, FNPT
1.5" / DN 40, FNPT

49lbs / 24.5kg**

Materials of Construction

Body
Impeller
O-ring(s)
Seal
Finish

**316 stainless steel
316 stainless steel
Viton
Ceramic/C, 304 SS, Viton
Cast stainless steel**

Motor

Horsepower
Efficiency
Speed
Material
Enclosure Type
Service Factor
Frame


**0.33 hp
Non-premium, 62%
3450 rpm
Carbon steel, painted
TEFC
1.5
56J**

Utilities Required

Phase/Hz/Voltage
FLA

**3/60/208:230-460v
2.4-1.6/0.8**

* Flow rate determined by fluid/gas, temperature and operating parameters.






**ROGUE
PUMP®**

MAX TRS-33S Pump Curve


ENGLISH UNITS



Fluid specific gravity 1.0 @ 70°F

0.33hp 230v-460v 3p 60Hz 3450rpm

METRIC UNITS



Fluid specific gravity 1.0 @ 21°C

0.33hp 230v-460v 3p 60Hz 3450rpm

* Flow rate determined by fluid/gas, temperature and operating parameters.

