



ROGUE

PUMP COMPANY®
A LIMITED LIABILITY COMPANY

MAX RGT-185FI SPECIFICATIONS

Pump Specifications

Flow-rate
 Liquid/Medium
 Suction Pressure
 Gas Dissolution (air)
 Discharge Pressure
 Shaft Seal Type
 Pump Mounting
 Impeller(s)
 Fitting Dimensions
 Inlet
 Outlet
 Gas Inlet
 Weight
 Pump
 Pump & Motor

English/Metric
185 gpm/700 lpm (approx*)
Liquid/gas
Flooded
148 cfh, 10% maximum
184ft/56m (80psi)
Mechanical seal
Flex coupled
Single stage

4"/DN 100, flanged
3"/DN 80, flanged
3/8" NPT/DN 10

631 lbs/286.2 kg
1068 lbs/484.4 kg

Materials of Construction

Body
 Shaft Sleeve
 Impeller
 O-ring(s)
 Seal
 Guard
 Coupling
 Base Mount
 Finish

Ductile iron
304 stainless steel
Carbon steel
Viton
Ceramic/C, 304 SS, Viton
304 stainless steel, safety yellow
Urethane high speed rings
Carbon steel
Metallic blue top-coat
Rust inhibited pre-coat

Motor

Horsepower
 Efficiency
 Speed
 Material
 Enclosure Type
 Service Factor
 Frame
 FLA

30 hp
Premium, 93.6%
1750 rpm
Carbon steel, painted
TEFC
1.15
286T
51-48/24

Utilities Required

Phase/Hz/Voltage

3/60/208:230-460v

* Flow rate determined by fluid/gas, temperature and operating parameters.




ROGUE

PUMP COMPANY®
A LIMITED LIABILITY COMPANY

MAX RGT-185 PUMP CURVE


ENGLISH UNITS



Fluid specific gravity 1.0 @ 70°F

30hp 230v-460v 3p 60Hz 1750rpm

METRIC UNITS



Fluid specific gravity 1.0 @ 21°C

30hp 230v-460v 3p 60Hz 1750rpm